INTERNATIONAL STANDARDS AND RECOMMENDED PRACTICES

OPERATION OF AIRCRAFT

ANNEX 6

TO THE CONVENTION ON INTERNATIONAL CIVIL AVIATION

PART II INTERNATIONAL GENERAL AVIATION — AEROPLANES

SIXTH EDITION OF PART II - JULY 1998



This edition incorporates all amendments adopted by the Council prior to 21 March 1998 and supersedes, on 5 November 1998, all previous editions of Part II of Annex 6.

For information regarding the applicability of the Standards and Recommended Practices, see Foreword.

INTERNATIONAL CIVIL AVIATION ORGANIZATION

Published in separate English, Arabic, French, Russian and Spanish editions by the International Civil Aviation Organization. All correspondence, except orders and subscriptions, should be addressed to the Secretary General.

Orders for this publication should be sent to one of the following addresses, together with the appropriate remittance (by bank draft, cheque or money order) in U.S. dollars or the currency of the country in which the order is placed.

Document Sales Unit Telephone: (514) 954-802	·Z
International Civil Aviation Organization Telex: 05-24513	
999 University Street Facsimile: (514) 954-6769)
Montreal, Quebec Sitatex: YULCAYA	
Canada H3C 5H7 Internet: sales_unit@icao.	org

Credit card orders (American Express, MasterCard and Visa) are accepted at the above address.

Egypt. ICAO Representative, Middle East Office, Egyptian Civil Aviation Complex, Cairo Airport Road, Heliopolis, Cairo 11776 Telephone: (20 2) 267-4840; Facsimile: (20 2) 267-4843; Sitatex: CAICAYA France. Représentant de l'OACI, Bureau Europe et Atlantique Nord, 3 bis, villa Émile-Bergerat, 92522 Neuilly-sur-Seine (Cedex) Téléphone: (33 1) 46 41 85 85; Télécopieur: (33 1) 46 41 85 00; Sitatex: PAREUYA India. Oxford Book and Stationery Co., Scindia House, New Delhi 110001 or 17 Park Street, Calcutta 700016 Telephone: (91 11) 331-5896; Facsimile: (91 11) 332-2639 Japan. Japan Civil Aviation Promotion Foundation, 15-12, 1-chome, Toranomon, Minato-Ku, Tokyo Telephone; (81 3) 3503-2686; Facsimile; (81 3) 3503-2689 Kenya. ICAO Representative, Eastern and Southern African Office, United Nations Accommodation, P.O. Box 46294, Nairobi Telephone: (254-2) 622-395; Facsimile: (254 2) 226-706; Sitatex: NBOCAYA Mexico. Representante de la OACI, Oficina Norteamérica, Centroamérica y Caribe, Masaryk No. 29-3er. piso, Col. Chapultepec Morales, México, D.F., 11570 Teléfono: (52 5) 250-3211; Facsímile: (52 5) 203-2757; Sitatex: MEXCAYA Peru. Representante de la OACI, Oficina Sudamérica, Apartado 4127, Lima 100 Teléfono: (51 14) 302260; Facsímile: (51 14) 640393; Sitatex: LIMCAYA Senegal. Représentant de l'OACI, Bureau Afrique occidentale et centrale, Boîte postale 2356, Dakar Téléphone; (221) 8-23-47-86; Télécopieur: (221) 8-23-69-26; Sitatex: DKRCAYA South Africa. Avex Air Training (Pty) Ltd., Private Bag X102, Halfway House, 1685, Republic of South Africa Telephone: (27-11) 315-0003/4; Facsimile: (27-11) 805-3649; Internet: avex@iafrica.com Spain. A.E.N.A. — Aeropuertos Españoles y Navegación Aérea, Calle Juan Ignacio Luca de Tena, 14, Planta Tercera, Despacho 3. 11, 28027 Madrid Teléfono: (34 1) 321-3148; Facsímile: (34 1) 321-3157; Internet: sscc.jcsoria@aena.es Thailand. ICAO Representative, Asia and Pacific Office, P.O. Box 11, Samyaek Ladprao, Bangkok 10901 Telephone; (66 2) 537-8189; Facsimile: (66 2) 537-8199; Sitatex: BKKCAYA

United Kingdom. Westward Digital Limited, 37 Windsor Street, Cheltenham, Glos., GL52 2DG Telephone: (44 1242) 235-151; Facsimile: (44 1242) 584-139

2/98

Catalogue of ICAO Publications and Audio-visual Training Aids

Issued annually, the Catalogue lists all publications and audio-visual training aids currently available.

Monthly supplements announce new publications and audio-visual training aids, amendments, supplements, reprints, etc.

Available free from the Document Sales Unit, ICAO

INTERNATIONAL STANDARDS AND RECOMMENDED PRACTICES

OPERATION OF AIRCRAFT

ANNEX 6

TO THE CONVENTION ON INTERNATIONAL CIVIL AVIATION

PART II INTERNATIONAL GENERAL AVIATION — AEROPLANES

SIXTH EDITION OF PART II — JULY 1998

This edition incorporates all amendments adopted by the Council prior to 21 March 1998 and supersedes, on 5 November 1998, all previous editions of Part II of Annex 6.

For information regarding the applicability of the Standards and Recommended Practices, see Foreword.

INTERNATIONAL CIVIL AVIATION ORGANIZATION

AMENDMENTS

The issue of amendments is announced regularly in the ICAO Journal and in the monthly Supplement to the Catalogue of ICAO Publications and Audio-Visual Training Aids, which holders of this publication should consult. The space below is provided to keep a record of such amendments.

RECORD OF AMENDMENTS AND CORRIGENDA

	AMENDMENTS			CORRIGENDA			·····	
No.	Date applicable	Date entered	Entered by		No.	Date of issue	Date entered	Entered by
1-18	 	ncorporated in thi	s Edition	1				
]				
		·	· · · · · · · · · · · · · · · · · · ·					
			· · · · · · · · · · · · · · · · · · ·	-		ļ	· · · ·	
				1		<u> </u>		
			····				+	
							·	· · · · · · · · · · · · · · · · · · ·
	· · · · · · · · · · · · · · · · · · ·							
]				
 	·	 		. 				
				4				
			· · · · · · · · · · · · · · · · · · ·					<u> </u>
·		<u></u>	· · · · · · · · · · · · · · · · · · ·			{		
	·			4				
	<u> </u>		······································					<u> </u>

(ii)

TABLE OF CONTENTS

(iii)

.

1 1460
1 1460

Abbreviations and symbols	(v)
Publications	(vi)
FOREWORD	(vii)
CHAPTER 1. Definitions	1
CHAPTER 2. Applicability	4
CHAPTER 3. General	5
CHAPTER 4. Flight preparation and in-flight	
procedures	6
A 1 A 1 and a feature for 11th	/
4.1 Adequacy of operating facilities	6
4.2 Actourome operating minima	6
4.4 Aeroplane airworthiness and safety	U
precautions	6
4.5 Weather reports and forecasts	6
4.6 Limitations imposed by weather	
conditions	7
4.7 Destination alternate aerodromes	7
4.8 Fuel and oil supply	7
4.9 Oxygen supply	7
4.10 Use of oxygen	8
4.11 In-flight emergency instruction	8
4.12 Weather reporting by pilots	8 0
4.15 Hazardous inght conditions	0
4.14 Flutess of high clew members at duty stations	0
4.16 Instrument flight procedures	8
4 17 Instruction — general	9
4.18 Refuelling with passengers on board	9
CHAPTER 5. Aeroplane performance operating	
limitations	10
equipment	11
6.1 All aeroplanes on all flights	[1
6.2 All aeroplanes operated as VFR flights	12
ANNEX 6 — PART U	(iii

6.3	All aeroplanes on flights over water	12
0.4	An aeropianes on rights over designated	12
65	All acception on high altitude flights	13
0.3	All aeropianes on mgn annude finghts	15
0.0	All aeropianes operated in accordance	10
<i>.</i> -	with the instrument flight rules	13
6./	All aeropianes when operated at hight	15
6.8	All aeroplanes complying with the noise	
r	certification Standards in Annex 16,	
	Volume 1	14
6.9	Accoplanes required to be equipped with	
	ground proximity warning systems	
	(GPWS)	14
6.10	Flight recorders.	14
6.11	Mach number indicator	16
6.12	Emergency locator transmitter	
	(ELT)	16
6.13	Aeroplanes required to be equipped with a	
	pressure-altitude reporting transponder	16
6.14	Microphones	16
navig: 7.1	Communication equipment	17 17 17
CHAPT	ER 8. Aeroplane maintenance	19
8.1	Responsibility	19
8.2	Qualification to certify as airworthy	19
8.3	Maintenance records	19
		20
CHAPT	EK 9. Aeropiane ingin crew	20
0.1	Qualifications	20
9.1	Composition of the flight arow	20
9.2	Composition of the hight crew	20
ΔΡΡΕΝΙ	DIX I jobts to be displayed by	
ALL LLA SPECT	anes	21
acrop	W100	<i>2</i> 1
1	Terminology	21
1.	Navigation lights to be displayed	21
2.	in the sir	21
	m mo an	<u></u>

Page

	Page	
3. Lights to be displayed on the water	21	3. Inspections of flight data and cockpit voice recorder systems
ATTACHMENT A. Flight recorders	25	ATTACHMENT B. Carriage and use of oxygen
Introduction	25	Introduction
1. Flight data recorder (FDR)	25	1. Oxygen supply
2. Cockpit voice recorder (CVR)	25	2. Use of oxygen

Part II

Page

26

31

31

31

31

.

ABBREVIATIONS AND SYMBOLS

(used in this Annex)

Abbreviations

Abbreviations

	Accident/incident reporting	GPWS	Ground proximity warning system
ADREE	Automatic flight control system	hPa	Hectonascal
AGA	Aerodromes air routes and ground aids	IFR	Instrument flight rules
AGA	Accident investigation and prevention	IMC	Instrument meteorological conditions
	A sig Desifie	INC	Inertial navigation systems
ASIA/PAC		ka	Kilogram
ATC		к <u></u> km	Kilometre
AIS	Air tranic services	Kill kan /h	Kilometres per hour
	Category I	KIIVII Let	Knomenes per nour
CAT II	Category II	KL	Kilot
CAT III	Category III		Miche dessent altitude
CAT IIIA	Category IIIA	MDA	Minimum descent altitude
CAT IIIB	Category IIIB	MDA/H	Minimum descent altitude/neight
CAT IIIC	Category IIIC	MDH	Minimum descent height
CFIT	Controlled flight into terrain	MHz	Megahertz
cm	Centimetre	MNPS	Minimum navigation performance specifications
CVR	Cockpit voice recorder	NAV	Navigation
DA	Decision altitude	NM	Nautical mile
DA/H	Decision altitude/height	N1	High pressure turbine speed
DH	Decision height	QCA	Obstacle clearance altitude
DME	Distance measuring equipment	OCA/H	Obstacle clearance altitude/height
ECAM	Electronic centralized aircraft monitor	OCH	Obstacle clearance height
EFIS	Electronic flight instrument system	RNP	Required navigation performance
EGT	Exhaust gas temperature	RVR	Runway visual range
EICAS	Engine indication and crew alerting system	SI	International System of Units
ELT	Emergency locator transmitter	SICASP	Secondary Surveillance Radar Improvements and
ELT(AF)	Automatic fixed ELT		Collision Avoidance Systems Panel
ELT(AP)	Automatic portable ELT	UTC	Universal co-ordinated time
ELT(AD)	Automatically deployable ELT	Vn	Design diving speed
ELT(S)	Survival ELT	VFR	Visual flight rules
EPR	Engine pressure ratio	VMC	Visual meteorological conditions
EUROCAE	European Organization for	VSM	Vertical separation minima
Dentecina	Civil Aviation Electronics	Ve	Stalling speed or the minimum steady flight speed
FDAU	Flight data acquisition unit	30	in the landing configuration
FDR	Flight data recorder	WXR	Weather
FI	Flight level		· · · · · · · · · · · · · · · · · · ·
FM	Frequency modulation	Symbols	
ft	Foot	°C	Degrees Celsius
	Normal acceleration	7	Per cent
Б		10	I VI VVIII

PUBLICATIONS

(referred to in this Annex)

Convention on International Civil Aviation (Doc 7300)

International Regulations for Preventing Collisions at Sea

European Organization for Civil Aviation Electronics (EUROCAE) Documents ED55 and ED56A

Nationality and Registration of Aircraft Operated by International Operating Agencies (Doc 8722) (Replaced by Policy and Guidance Material on the Regulation of International Air Transport (Doc 9587))

Annexes to the Convention on International Civil Aviation

Annex 1 — Personnel Licensing

Annex 2 - Rules of the Air

Annex 3 - Meteorological Service for International Air Navigation

Annex 5 — Units of Measurement to be Used in Air and Ground Operations

Annex 6 — Operation of Aircraft Part I — International Commercial Air Transport — Aeroplanes Part III — International Operations — Helicopters

Annex 8 — Airworthiness of Aircraft

Annex 10 — Aeronautical Telecommunications Volume III (Part I — Digital Data Communication Systems, Part II — Voice Communication Systems) Volume IV (Surveillance Radar and Collision Avoidance Systems)

Annex 11 — Air Traffic Services

Annex 12 - Search and Rescue

Annex 13 — Aircraft Accident Investigation

Annex 14 — Aerodromes Volume I — Aerodrome Design and Operations Annex 15 — Aeronautical Information Services

Annex 16 — Environmental Protection Volume I — Aircraft Noise

Annex 18 — The Safe Transport of Dangerous Goods by Air

Procedures for Air Navigation Services

OPS — Aircraft Operations (Doc 8168) Volume I — Flight Procedures Volume II — Construction of Visual and Instrument Flight Procedures

RAC — Rules of the Air and Air Traffic Services (Doc 4444)

Protocol Relating to an Amendment to the Convention on International Civil Aviation (Article 83 bis) (Doc 9318)

Regional Supplementary Procedures (Doc 7030)

Manuals

Accident/Incident Reporting Manual (ADREP Manual) (Doc 9156)

Airport Services Manual (Doc 9137) Part 1 — Rescue and Fire Fighting Part 8 — Airport Operational Services

Airworthiness Technical Manual (Doc 9051)

Manual of Civil Aviation Medicine (Doc 8984)

Manual on Implementation of a 300 m (1 000 ft) Vertical Separation Minimum Between FL290 and FL410 Inclusive (Doc 9574)

Manual on Required Navigation Performance (RNP) (Doc 9613)

ANNEX 6 — PART II INTERNATIONAL GENERAL AVIATION — AEROPLANES

FOREWORD

Historical background

Standards and Recommended Practices for the Operation of Aircraft — International General Aviation were first adopted by the Council on 2 December 1968 pursuant to the provisions of Article 37 of the Convention on International Civil Aviation (Chicago, 1944) and designated as Annex 6, Part II, to the Convention. They became effective on 2 April 1969 and applicable on 18 September 1969.

Annex 6, Part II, was developed in the following manner: the Fifteenth Session of the Assembly, Montreal, June-July 1965, adopted Resolution A15-15: "Consideration of the needs of international general aviation in relation to the scope of ICAO technical activities". Subsequently, the Fourth Air Navigation Conference (Montreal, November-December 1965) recommended a series of factors which it considered should be taken into account in extending the scope of Annex 6 to meet the needs of general aviation in accordance with the directives of Assembly Resolution A15-15.

The Fourth Air Navigation Conference recommended that the International Standards and Recommended Practices to be developed for International General Aviation Operations exclude for the present aerial work operations. It was however clearly the view of the conference that the Annex should be framed in such a manner as to facilitate its extension to cover aerial work operations at a later date, should such extension prove desirable.

Based on the above considerations, draft International Standards and Recommended Practices for the Operation of International General Aviation Aircraft were developed by the Air Navigation Commission and, after amendment following the usual consultation with the Member States of the Organization, were adopted by the Council so as to become, together with the Foreword approved by the Council, the text of this Annex. In developing this material the Air Navigation Commission was guided by the following philosophies:

Presentation and conformity with Annex 6, Part I. The Annex should be, as nearly as practicable, equivalent in scope and conform as closely as possible to Annex 6 (now Annex 6, Part I). Applicability. Although the definition of general aviation originally used in this Annex encompassed aerial work operations, these were specifically excluded from the provisions of this Annex by Chapter 2 — Applicability.

Level of safety. The Annex should ensure an acceptable level of safety to third parties (third parties meaning persons on the ground and persons in the air in other aircraft). Also, as some international general aviation operations will be performed:

- a) by crews less experienced and less skilled;
- b) by less reliable equipment;
- c) to less rigorous standards; and
- d) with greater freedom of action than in commercial air transport operations;

it has to be accepted that the passenger in international general aviation aircraft will not necessarily enjoy the same level of safety as the fare-paying passenger in commercial air transport. However, it was recognized that in ensuring an acceptable degree of safety for third parties, an acceptable level of safety for flight crews and passengers would be achieved.

Freedom of Action. The maximum freedom of action consistent with maintaining an acceptable level of safety should be granted to international general aviation.

Responsibility. The responsibility that devolves upon the operator in Annex 6, Part I, should, in Part II of the Annex, fall upon the pilot-in-command. Precedent for this course of action exists in Annex 2.

Consequent to the adoption of Annex 6, Part III, International Operations — Helicopters, an amendment to the title was introduced to indicate that Annex 6, Part II was applicable only to aeroplanes.

In 1986 the Air Navigation Commission commenced a review of Annex 6, Part II and concluded that the definition of general aviation should be revised to exclude aerial work thus recognizing that aerial work was a distinct aspect of civil aviation and recognizing the exclusion of aerial work from the applicability of Annex 6, Part II. As with the Fourth Air Navigation Conference in 1965, the Air Navigation Commission was not aware of any degree of international aerial work operations which would necessitate the development of International Standards and Recommended Practices. The revised definitions for general aviation and aerial work and the revised applicability chapter were submitted to States in the usual manner and approved by the Council in March 1990.

Table A shows the origin of amendments together with a list of the principal subjects involved and the dates on which the Annex and the amendments were adopted by the Council, when they became effective and when they became applicable.

Applicability

The Standards and Recommended Practices of Annex 6, Part II are applicable to international general aviation operations with aeroplanes.

The Standards and Recommended Practices represent minimum provisions and, together with those of Annex 6 — Operation of Aircraft: Part I — International Commercial Air Transport — Aeroplanes, now cover the operation of all aeroplanes in international civil aviation, except in aerial work operations.

It will be noted that the Standards and Recommended Practices contained in Annex 6, Part II, when applied to the operation of large aeroplanes, are less stringent than those in Annex 6, Part I, applicable to the same or similar aeroplanes when used in commercial air transport operations. Nevertheless, it is considered that, in conjunction with existing provisions in Annexes 1 and 8, Annex 6, Part II, ensures an adequate level of safety for the operations envisaged for the large aeroplanes in question. In this connexion attention is drawn to the point that the entire performance standards of Annex 8 are applicable to all aeroplanes of over 5 700 kg mass intended for the carriage of passengers or cargo or mail for international air navigation, of which the prototype was submitted for certification on or after 13 December 1964. Moreover, by virtue of Annex 1 the holder of a private pilot licence, piloting an aircraft in excess of 5 700 kg unless as the sole occupant thereof is required to have a type rating entered on his licence. Since the certificates of airworthiness of the types of aeroplanes in question would preclude solo flight in all normal circumstances, it may be accepted that the private pilot of these aeroplanes must have a type rating entered on his licence.

Action by Contracting States

Notification of differences. The attention of Contracting States is drawn to the obligation imposed by Article 38 of the Convention by which Contracting States are required to notify the Organization of any differences between their national regulations and practices and the International Standards contained in this Annex and any amendments thereto. Contracting States are invited to extend such notification to any differences from the Recommended Practices contained in this Annex, and any amendments thereto, when the notification of such differences is important for the safety of air navigation. Further, Contracting States are invited to keep the Organization currently informed of any differences which may subsequently occur, or of the withdrawal of any differences previously notified. A specific request for notification of differences will be sent to Contracting States immediately after the adoption of each amendment to this Annex.

The attention of States is also drawn to the provision of Annex 15 related to the publication of differences between their national regulations and practices and the related ICAO Standards and Recommended Practices through the Aeronautical Information Service, in addition to the obligation of States under Article 38 of the Convention.

Promulgation of information. The establishment and withdrawal of and changes to facilities, services and procedures affecting aircraft operations provided in accordance with the Standards and Recommended Practices specified in this Annex should be notified and take effect in accordance with the provisions of Annex 15.

Status of Annex components

An Annex is made up of the following component parts, not all of which, however, are necessarily found in every Annex; they have the status indicated:

- 1.--Material comprising the Annex proper:
 - a) Standards and Recommended Practices adopted by the Council under the provisions of the Convention. They are defined as follows:

Standard: Any specification for physical characteristics, configuration, matériel, performance, personnel or procedure, the uniform application of which is recognized as necessary for the safety or regularity of international air navigation and to which Contracting States will conform in accordance with the Convention; in the event of impossibility of compliance, notification to the Council is compulsory under Article 38.

Recommended Practice: Any specification for physical characteristics, configuration, matériel, performance, personnel or procedure, the uniform application of which is recognized as desirable in the interest of safety, regularity or efficiency of international air navigation, and to which Contracting States will endeavour to conform in accordance with the Convention.

- b) Appendices comprising material grouped separately for convenience but forming part of the Standards and Recommended Practices adopted by the Council.
- c) Definitions of terms used in the Standards and Recommended Practices which are not selfexplanatory in that they do not have accepted dictionary meanings. A definition does not have independent status but is an essential part of each Standard and Recommended Practice in which the term is used, since a change in the meaning of the term would affect the specification.
- d) *Tables* and *Figures* which add to or illustrate a Standard or Recommended Practice and which are referred to therein, form part of the associated Standard or Recommended Practice and have the same status.

It is to be noted that some Standards in this Annex incorporate, by reference, other specifications having the status of Recommended Practices. In such cases, the text of the Recommended Practice becomes part of the Standard.

2.— Material approved by the Council for publication in association with the Standards and Recommended Practices:

- a) *Forewords* comprising historical and explanatory material based on the action of the Council and including an explanation of the obligations of States with regard to the application of the Standards and Recommended Practices ensuing from the Convention and the Resolution of Adoption;
- b) *Introductions* comprising explanatory material introduced at the beginning of parts, chapters or sections of the Annex to assist in the understanding of the application of the text;
- c) *Notes* included in the text, where appropriate, to give factual information or references bearing on the Standards or Recommended Practices in question, but not constituting part of the Standards or Recommended Practices;

d) Attachments comprising material supplementary to the Standards and Recommended Practices, or included as a guide to their application.

Selection of language

This Annex has been adopted in five languages — English, Arabic, French, Russian and Spanish. Each Contracting State is requested to select one of those texts for the purpose of national implementation and for other effects provided for in the Convention, either through direct use or through translation into its own national language, and to notify the Organization accordingly.

Editorial practices

The following practice has been adhered to in order to indicate at a glance the status of each statement: *Standards* have been printed in light face roman; *Recommended Practices* have been printed in light face italics, the status being indicated by the prefix **Recommendation**; *Notes* have been printed in light face italics, the status being indicated by the prefix *Note*.

The following editorial practice has been followed in the writing of specifications: for Standards the operative verb "shall" is used, and for Recommended Practices the operative verb "should" is used.

The units of measurement used in this document are in accordance with the International System of Units (SI) as specified in Annex 5 to the Convention on International Civil Aviation. Where Annex 5 permits the use of non-SI alternative units these are shown in parentheses following the basic units. Where two sets of units are quoted it must not be assumed that the pairs of values are equal and interchangeable. It may, however, be inferred that an equivalent level of safety is achieved when either set of units is used exclusively.

Any reference to a portion of this document, which is identified by a number and/or title, includes all subdivisions of that portion.

Table A.	Amendments to Annex 6. Part II
1001011	international to runter v, i are in

Amendment	Source(s)	Subject(s)	Adopted Effective Applicable
1st Edition	Fifteenth Session of the Assembly (Resolution A15-15) and Fourth Air Navigation Conference		2 December 1968 2 April 1969 18 September 1969
1	Sixth Air Navigation Conference	 a) The requirement for additional instruments in aeroplanes operated as controlled VFR flights in the en-route phase; and b) the permitting of aeroplanes, when unable to navigate by visual references to landmarks, to be navigated by equipment other than radio navigation equipment, e.g. solely by self-contained navigation means, provided that certain equipment capabilities are met, thus eliminating any requirement for the carriage of radio navigation equipment. 	1 June 1970 1 October 1970 4 February 1971
2 (2nd Edition)	Special Meeting on Aircraft Noise in the Vicinity of Aerodromes	The inclusion of a specification for aeroplanes to be operated within the weight limitations imposed by the applicable Noise Certification Standards, except in prescribed circumstances, and to carry a document attesting noise certification.	2 April 1971 2 August 1971 6 January 1972
3	Seventh Air Navigation Conference	The inclusion of a Recommended Practice covering the design, carriage and installation of Emergency Location Beacons — Aircraft, in such aeroplanes and on such flights as may be determined by the appropriate authority.	29 May 1973 1 October 1973 23 May 1974
4	Revision of Annex 12, the Air Navigation Commission's Study concerning interception of civil aircraft and the Council action in pursuance of Assembly Resolution A18-16	 a) Provisions for the marking of break-in points on aircraft; b) provisions for reducing the risk for intercepted aircraft; c) the revision of the Introductory Note to Chapter 3 of the Annex. The revision points to a practical method for States to discharge their functions in the cases of lease, charter and interchange of aircraft in international operations. 	4 February 1975 4 June 1975 9 October 1975
5	Studies by the Air Navigation Commission, Amendment 60 to Annex 3 and Amendment 30 to Annex 14	Requirements for the provision and use of flight crew safety harnesses; amplification of specifications for the type of timepiece required for operations in accordance with Instrument Flight Rules and controlled VFR flights; and revision of the definitions of Aerodrome and Meteorological information.	7 April 1976 7 August 1976 30 December 1976
6	ASIA/PAC Regional Air Navigation Meeting	The requirement for the carriage of survival radio equipment over those areas in which search and rescue would be especially difficult to be determined by States rather than regional air navigation agreement.	16 June 1976 16 October 1976 6 October 1977
7	Air Navigation Commission Study	Recommendation for the fitting of ground proximity warning systems to certain aeroplanes.	15 December 1977 15 April 1978 10 August 1978

Amendment	Source(s)	Subject(s)	Adopted Effective Applicable
8	Air Navigation Commission Study	Introduction of requirements for navigation equipment to meet minimum navigational performance specifications (MNPS).	2 April 1980 2 August 1980 27 November 1980
9	Air Navigation Commission Study	Revision of the provisions relating to exterior lights to align with new provisions in Annexes 2 and 8.	22 March 1982 22 July 1982 25 November 1982
10 (3rd Edition)	Seventh meeting of the Obstacle Clearance Panel, AGA Divisional Meeting (1981), amendments consequential to adoption of Annexes 5 and 18	Introduced provisions related to development and use of instrument approach procedures, authority and competence to taxi aeroplanes. Changes to the requirements for the carriage of dangerons goods as a result of adoption by the Council of Annex 18. Units of measurement were brought in line with the provisions of Annex 5 and the <i>Note</i> in Chapter 3 concerning lease, charter and interchange was updated. The term "aerodrome operating minima" was introduced in lieu of "aerodrome meteorological minima", and definitions of "decision altitude/height" and "minimum descent altitude/height" entered in Chapter 1.	20 May 1983 20 September 1983 24 November 1983
11	Accident Prevention and Investigation Divisional Meeting, AIG (1979)	Introduction of provisions relating to flight recorders. Introduction of related guidance material in an attachment.	8 March 1985 29 July 1985 21 November 1985
12	Air Navigation Commission	Carriage of information on board aircraft; communication equipment on 121.5 MHz.	14 March 1986 27 July 1986 20 November 1986
13	Seventh meeting of the Obstacle Clearance Panel, Air Navigation Commission studies	Supply and use of oxygen and pressurization failure warning; refuelling with passengers on board; provision of climb performance data with all engines operating.	14 March 1986 27 July 1986 20 November 1986
14 (4th Edition)	Air Navigation Commission review of the Annex, Stage I, Third meeting of the Visual Flight	a) Revision of the definitions of aerial work and general aviation. Revision of the definition of alternate aerodrome to introduce take-off, en-route and destination alternate aerodromes. Introduction of a new definition for a commercial air transport operation and the definitions for flight plan and flight recorder;	19 March 1990 30 July 1990 15 November 1990
	Rules Operations	b) deletion of the reference to aerial work from the applicability;	
	Air Navigation Commission Study	c) alignment with Annex 6, Part I, particularly with respect to flight recorder records subsequent to accidents or incidents and the requirement for a Mach number indicator;	
		d) elimination of the term "controlled VFR flight";	
		e) introduction of guidance material concerning flight data recording of important operational information in aeroplanes with electronic displays.	

Part II

Amendment	Source(s)	Subject(s)	Adopted Effective Applicable
15	Fifth meeting of the Operations Panel, Seventh and Eighth meetings of the	 Revision of definitions of aerodrome operating minima, decision altitude height, minimum descent altitude/height and introduction of definition of obstacle clearance altitude/height; 	/ 21 March 1994 25 July 1994 10 November 1994
	Review of the General Concept of	b) introduction of new definitions for emergency locator transmitters (ELTs required navigation performance (RNP) and RNP type;	I
	Accident Investigation Divisional Meeting (AIG/1992).	c) introduction of the definition for the classification of instrument approach and landing operations;	ч.,
	Air Navigation Commission studies	d) revision of the requirements concerning the use of engraving metal foil flight data recorders;	
		 introduction of carriage requirements for emergency locator transmitters (ELTs) to replace provisions regarding survival radio equipment and emergency location beacon; 	
		f) introduction of a requirement that the navigation equipment carried shall enable the aircraft to proceed in accordance with RNP types prescribed for the intended route(s) or area(s) and provisions to permit the uniform implementation of 300 m (1 000 ft) VSM above FL 290.	
16 (5th Edition)	Air Navigation Commission studies,	a) Introduction of revised definitions;	10 March 1995 24 July 1995
	Fourteenth meeting of the Dangerous Goods	b) inclusion of references to Article 35 of the Convention;	9 November 1995
	Panel, editorial amendment, text alignment with Annex 6, Part I and/or	c) revision of the provisions concerning operating facilities, briefing, aeroplane airworthiness and safety precautions, destination alternate aerodromes, limitations imposed by weather conditions, use of oxygen and safety harness;	
	amendment	 new provisions concerning all aeroplanes on all flights, all aeroplanes operated as VFR flights and ground proximity warning systems (GPWS) 	;
		e) revision of the provisions concerning aeroplanes operated in accordance with instrument flight rules (IFR);	
		f) revision of the provisions concerning the composition of the flight crew and	
		g) revision of the provisions concerning the carriage and use of oxygen.	
17	Fourth meeting of the Secondary Surveillance Radar Improvements and Collision Avoidance Systems Panel (SICASP/4)	Requirement for aeroplanes to be equipped with pressure-altitude reporting transponders.	19 February 1996 15 July 1996 7 November 1996

Amendment	Source(s)		Subject(s)	Adopted Effective Applicable
18 (6th Edition)	First meeting of the Flight Recorder Panel, ICAO and Industry	a)	Introduction of new and revised definitions for psychoactive substances and required navigation performance;	20 March 1998 20 July 1998 5 November 1998
	CFIT Task Force, Air Navigation Commission	b) 1	revision of the notes concerning lease and interchange;	
	studies, Amendment 162 to Annex 1,	C)	introduction of a note concerning use of psychoactive substances; and	
	Amendment 38 to Annex 11, editorial amendment	d)	new and revised provisions concerning ground proximity warning systems, pressure-altitude reporting transponders and flight recorders.	

INTERNATIONAL STANDARDS AND RECOMMENDED PRACTICES

CHAPTER 1. DEFINITIONS

When the following terms are used in the Standards, Recommended Practices and Definitions for the operation of aeroplanes in international general aviation, they have the following meanings:

- Aerial work. An aircraft operation in which an aircraft is used for specialized services such as agriculture, construction, photography, surveying, observation and patrol, search and rescue, aerial advertisement, etc.
- Aerodrome. A defined area on land or water (including any buildings, installations and equipment) intended to be used either wholly or in part for the arrival, departure and surface movement of aircraft.
- Aerodrome operating minima. The limits of usability of an aerodrome for:
 - a) take-off, expressed in terms of runway visual range and/or visibility and, if necessary, cloud conditions;
 - b) landing in precision approach and landing operations, expressed in terms of visibility and/or runway visual range and decision altitude/height (DA/H) as appropriate to the category of the operation; and
 - c) landing in non-precision approach and landing operations, expressed in terms of visibility and/or runway visual range, minimum descent altitude/height (MDA/H) and, if necessary, cloud conditions.
- Aeroplane. A power-driven heavier-than-air aircraft, deriving its lift in flight chiefly from aerodynamic reactions on surfaces which remain fixed under given conditions of flight.
- Aircraft. Any machine that can derive support in the atmosphere from the reactions of the air other than the reactions of the air against the earth's surface.
- Alternate aerodrome. An aerodrome to which an aircraft may proceed when it becomes either impossible or inadvisable to proceed to or to land at the aerodrome of intended landing. Alternate aerodromes include the following:
 - Take-off alternate. An alternate aerodrome at which an aircraft can land should this become necessary shortly after take-off and it is not possible to use the aerodrome of departure.

- *En-route alternate.* An aerodrome at which an aircraft would be able to land after experiencing an abnormal or emergency condition while en route.
- Destination alternate. An alternate aerodrome to which an aircraft may proceed should it become either impossible or inadvisable to land at the aerodrome of intended landing.

Note.— The aerodrome from which a flight departs may also be an en-route or a destination alternate aerodrome for that flight.

- *Commercial air transport operation.* An aircraft operation involving the transport of passengers, cargo or mail for remuneration or hire.
- *Dangerous goods.* Articles or substances which are capable of posing significant risk to health, safety or property when transported by air.

Note 1.— Dangerous goods are classified in Annex 18, Chapter 3.

Decision altitude (DA) or **decision height (DH)**. A specified altitude or height in the precision approach at which a missed approach must be initiated if the required visual reference to continue the approach has not been established.

Note I.— Decision altitude (DA) is referenced to mean sea level and decision height (DH) is referenced to the threshold elevation.

Note 2.— The required visual reference means that section of the visual aids or of the approach area which should have been in view for sufficient time for the pilot to have made an assessment of the aircraft position and rate of change of position, in relation to the desired flight path. In Category III operations with a decision height the required visual reference is that specified for the particular procedure and operation.

Note 3.— For convenience where both expressions are used they may be written in the form "decision altitude/height" and abbreviated "DA/H".

Emergency locator transmitter (ELT). A generic term describing equipment which broadcast distinctive signals on designated frequencies and, depending on application,

Annex 6 — Operation of Aircraft

may either sense a crash and operate automatically or be manually activated. An ELT may be any of the following:

- Automatic fixed ELT (ELT(AF)). An ELT which is permanently attached to an aircraft.
- Automatic portable ELT (ELT(AP)). An ELT which is rigidly attached to an aircraft but readily removable from the aircraft after a crash.
- Automatically deployable ELT (ELT(AD)). An ELT which is rigidly attached to an aircraft and deployed automatically in response to a crash. Manual deployment is also provided.
- Survival ELT (ELT(S)). An ELT which is removable from an aircraft, stowed so as to facilitate its ready use in an emergency and activated by survivors. Automatic activation may apply.
- Flight crew member. A licensed crew member charged with duties essential to the operation of an aircraft during flight time.
- Flight manual. A manual, associated with the certificate of airworthiness, containing limitations within which the aircraft is to be considered airworthy, and instructions and information necessary to the flight crew members for the safe operation of the aircraft.
- Flight plan. Specified information provided to air traffic services units, relative to an intended flight or portion of a flight of an aircraft.
- *Flight recorder.* Any type of recorder installed in the aircraft for the purpose of complementing accident/incident investigation.
- Flight time. The total time from the moment an aircraft first moves under its own power for the purpose of taking off until the moment it comes to rest at the end of the flight.

Note.— Flight time as here defined is synonymous with the term "block to block" time or "chock to chock" time in general usage which is measured from the time an aircraft moves from the loading point until it stops at the unloading point.

- General aviation operation. An aircraft operation other than a commercial air transport operation or an aerial work operation.
- Instrument approach and landing operations. Instrument approach and landing operations using instrument approach procedures are classified as follows:
 - Non-precision approach and landing operations. An instrument approach and landing which does not utilize electronic glide path guidance.

Precision approach and landing operations. An instrument approach and landing using precision azimuth and glide path guidance with minima as determined by the category of operation.

Categories of precision approach and landing operations:

- Category I (CAT I) operation. A precision instrument approach and landing with a decision height not lower than 60 m (200 ft) and with either a visibility not less than 800 m or a runway visual range not less than 550 m.
- Category II (CAT II) operation. A precision instrument approach and landing with a decision height lower than 60 m (200 ft), but not lower than 30 m (100 ft), and a runway visual range not less than 350 m.
- Category IIIA (CAT IIIA) operation. A precision instrument approach and landing with:
 - a) a decision height lower than 30 m (100 ft) or no decision height; and
 - b) a runway visual range not less than 200 m.
- Category IIIB (CAT IIIB) operation. A precision instrument approach and landing with:
 - a) a decision height lower than 15 m (50 ft) or no decision height; and
 - b) a runway visual range less than 200 m but not less than 50 m.
- Category IIIC (CAT IIIC) operation. A precision instrument approach and landing with no decision height and no runway visual range limitations.

Note.— Where decision height (DH) and runway visual range (RVR) fall into different categories of operation, the instrument approach and landing operation would be conducted in accordance with the requirements of the most demanding category (e.g. an operation with a DH in the range of CAT IIIA but with an RVR in the range of CAT IIIB would be considered a CAT IIIB operation or an operation with a DH in the range of CAT II but with an RVR in the range of CAT I would be considered a CAT II operation).

Instrument meteorological conditions (IMC). Meteorological conditions expressed in terms of visibility, distance from cloud, and ceiling*, less than the minima specified for visual meteorological conditions.

Note.— The specified minima for visual meteorological conditions are contained in Chapter 4 of Annex 2.

^{*}As defined in Annex 2.

Chapter 1

- *Meteorological information.* Meteorological report, analysis, forecast, and any other statement relating to existing or expected meteorological conditions.
- Minimum descent altitude (MDA) or minimum descent height (MDH). A specified altitude or height in a non-precision approach or circling approach below which descent must not be made without the required visual reference.

Note 1.— Minimum descent altitude (MDA) is referenced to mean sea level and minimum descent height (MDH) is referenced to the aerodrome elevation or to the threshold elevation if that is more than 2 m (7 ft) below the aerodrome elevation. A minimum descent height for a circling approach is referenced to the aerodrome elevation.

Note 2.— The required visual reference means that section of the visual aids or of the approach area which should have been in view for sufficient time for the pilot to have made an assessment of the aircraft position and rate of change of position, in relation to the desired flight path. In the case of a circling approach the required visual reference is the runway environment.

Note 3.— For convenience when both expressions are used they may be written in the form "minimum descent altitude/height" and abbreviated "MDA/H".

Night. The hours between the end of evening civil twilight and the beginning of morning civil twilight or such other period between sunset and sunrise, as may be prescribed by the appropriate authority.

Note.— Civil twilight ends in the evening when the centre of the sun's disc is 6 degrees below the horizon and begins in the morning when the centre of the sun's disc is 6 degrees below the horizon.

Obstacle clearance altitude (OCA) or **obstacle clearance height (OCH).** The lowest altitude or the lowest height above the elevation of the relevant runway threshold or the aerodrome elevation as applicable, used in establishing compliance with appropriate obstacle clearance criteria.

Note 1.— Obstacle clearance altitude is referenced to mean sea level and obstacle clearance height is referenced to the threshold elevation or in the case of non-precision approaches to the aerodrome elevation or the threshold elevation if that is more than 2 m (7 ft) below the aerodrome elevation. An obstacle clearance height for a circling approach is referenced to the aerodrome elevation. Note 2.— For convenience when both expressions are used they may be written in the form "obstacle clearance altitude/height" and abbreviated "OCA/H".

- *Pilot-in-command.* The pilot responsible for the operation and safety of the aircraft during flight time.
- *Psychoactive substances.* Alcohol, opioids, cannabinoids, sedatives and hypnotics, cocaine, other psychostimulants, hallucinogens, and volatile solvents, whereas coffee and tobacco are excluded.
- **Required navigation performance (RNP).** A statement of the navigation performance necessary for operation within a defined airspace.

Note.— Navigation performance and requirements are defined for a particular RNP type and/or application.

RNP type. A containment value expressed as a distance in nautical miles from the intended position within which flights would be for at least 95 per cent of the total flying time.

Example.— RNP 4 represents a navigation accuracy of plus or minus 7.4 km (4 NM) on a 95 per cent containment basis.

- **Runway visual range (RVR).** The range over which the pilot of an aircraft on the centre line of a runway can see the runway surface markings or the lights delineating the runway or identifying its centre line.
- State of Registry. The State on whose register the aircraft is entered.

Note.— In the case of the registration of aircraft of an international operating agency on other than a national basis, the States constituting the agency are jointly and severally bound to assume the obligations which, under the Chicago Convention, attach to a State of Registry. See, in this regard, the Council Resolution of 14 December 1967 on Nationality and Registration of Aircraft Operated by International Operating Agencies (Doc 8722).

Visual meteorological conditions (VMC). Meteorological conditions expressed in terms of visibility, distance from cloud, and ceiling, equal to or better than specified minima.

Note.— The specified minima are contained in Annex 2.

CHAPTER 2. APPLICABILITY

The Standards and Recommended Practices contained in Annex 6, Part II shall be applicable to international general aviation operations with aeroplanes.

Note 1.— Standards and Recommended Practices applicable to the operation of aeroplanes by operators authorized to conduct international commercial air transport operations are to be found in Annex 6, Part I.

Note 2.— Standards and Recommended Practices applicable to international commercial air transport operations or international general aviation operations with helicopters are to be found in Annex 6, Part III.

CHAPTER 3. GENERAL

Note 1.— Although the Convention on International Civil Aviation allocates to the State of Registry certain functions which that State is entitled to discharge, or obligated to discharge, as the case may be, the Assembly recognized, in Resolution A23-13, that the State of Registry may be unable to fulfil its responsibilities adequately in instances where aircraft are leased, chartered or interchanged — in particular without crew - by an operator of another State and that the Convention may not adequately specify the rights and obligations of the State of an operator in such instances until such time as Article 83 bis of the Convention enters into force. Accordingly, the Council urged that if, in the above-mentioned instances, the State of Registry finds itself unable to discharge adequately the functions allocated to it by the Convention, it delegate to the State of the Operator, subject to acceptance by the latter State, those functions of the State of Registry that can more adequately be discharged by the State of the Operator. It was understood that pending entry into force of Article 83 bis of the Convention the foregoing action would only be a matter of practical convenience and would not affect either the provisions of the Chicago Convention prescribing the duties of the State of Registry or any third State. However, as Article 83 bis of the Convention entered into force on 20 June 1997, such transfer agreements will have effect in respect of Contracting States which have ratified the related Protocol (Doc 9318) upon fulfilment of the conditions established in Article 83 bis.

Note 2.— In the case of international operations effected jointly with aeroplanes not all of which are registered in the same Contracting State, nothing in this Part prevents the States concerned entering into an agreement for the joint exercise of the functions placed upon the State of Registry by the provisions of the relevant Annexes.

3.1 The pilot-in-command shall comply with the relevant laws, regulations and procedures of the States in which the aeroplane is operated.

Note 1.— Compliance with more restrictive measures, not in contravention of the provisions of 3.1, may be required by the State of Registry.

Note 2.— Rules covering flight over the high seas are contained in Annex 2.

3.2 The pilot-in-command shall be responsible for the operation and safety of the aeroplane and for the safety of all persons on board, during flight time.

3.3 If an emergency situation which endangers the safety of the aeroplane or persons necessitates the taking of action which involves a violation of local regulations or procedures, the pilot-in-command shall notify the appropriate local authority without delay. If required by the State in which the incident occurs, the pilot-in-command shall submit a report on any such violation to the appropriate authority of such State; in that event, the pilot-in-command shall also submit a copy of it to the State of Registry. Such reports shall be submitted as soon as possible and normally within ten days.

3.4 The pilot-in-command shall be responsible for notifying the nearest appropriate authority by the quickest available means of any accident involving the aeroplane resulting in serious injury or death of any person or substantial damage to the aeroplane or property.

Note.— A definition of the term "serious injury" is contained in Annex 13, and an explanation of the term "substantial damage" is given in the Accident/Incident Reporting Manual (ADREP Manual) (Doc 9156).

3.5 **Recommendation.**— The pilot-in-command should have available on board the aeroplane essential information concerning the search and rescue services in the areas over which it is intended the aeroplane will be flown.

3.6 Dangerous goods.

Note 1.— Provisions for carriage of dangerous goods are contained in Annex 18.

Note 2.— Article 35 of the Convention refers to certain classes of cargo restrictions.

3.7 Use of psychoactive substances.

Note.— Provisions concerning the use of psychoactive substances are contained in Annex 1, 1.2.7 and Annex 2, 2.5.

CHAPTER 4. FLIGHT PREPARATION AND IN-FLIGHT PROCEDURES

4.1 Adequacy of operating facilities

The pilot-in-command shall not commence a flight unless it has been ascertained by every reasonable means available that the ground and/or water areas and facilities available and directly required for such flight and for the safe operation of the aeroplane are adequate, including communication facilities and navigation aids.

Note.— "Reasonable means" in this Standard is intended to denote the use, at the point of departure, of information available to the pilot-in-command either through official information published by the aeronautical information services or readily obtainable from other sources.

4.2 Aerodrome operating minima

The pilot-in-command shall not operate to or from an aerodrome using operating minima lower than those which may be established for that aerodrome by the State in which it is located, except with the specific approval of that State.

Note.— It is the practice in some States to declare, for flight planning purposes, higher minima for an aerodrome when nominated as an alternate, than for the same aerodrome when planned as that of intended landing.

4.3 Briefing

4.3.1 The pilot-in-command shall ensure that crew members and passengers are made familiar, by means of an oral briefing or by other means, with the location and the use of:

- a) seat belts; and, as appropriate,
- b) emergency exits;
- c) life jackets;
- d) oxygen dispensing equipment; and
- e) other emergency equipment provided for individual use, including passenger emergency briefing cards.

4.3.2 The pilot-in-command shall ensure that all persons on board are aware of the location and general manner of use of the principal emergency equipment carried for collective use.

4.4 Aeroplane airworthiness and safety precautions

4.4.1 A flight shall not be commenced until the pilot-incommand is satisfied that:

- a) the aeroplane is airworthy, duly registered and that appropriate certificates with respect thereto are aboard the aeroplane;
- b) the instruments and equipment installed in the aeroplane are appropriate, taking into account the expected flight conditions;
- c) any necessary maintenance has been performed in accordance with Chapter 8;
- d) the mass of the aeroplane and centre of gravity location are such that the flight can be conducted safely, taking into account the flight conditions expected;
- e) any load carried is properly distributed and safely secured; and
- f) the aeroplane operating limitations, contained in the flight manual, or its equivalent, will not be exceeded.

4.4.2 **Recommendation.**— The pilot-in-command should have sufficient information on climb performance with all engines operating to enable determination of the climb gradient that can be achieved during the departure phase for the existing take-off conditions and intended take-off technique.

4.5 Weather reports and forecasts

Before commencing a flight the pilot-in-command shall be familiar with all available meteorological information appropriate to the intended flight. Preparation for a flight away from the vicinity of the place of departure, and for every flight under the instrument flight rules, shall include: 1) a study of available current weather reports and forecasts; and 2) the planning of an alternative course of action to provide for the eventuality that the flight cannot be completed as planned, because of weather conditions.

Note.— The requirements for flight plans are contained in Annex 2 — Rules of the Air and Procedures for Air Navigation Services — Rules of the Air and Air Traffic Services (PANS-RAC, Doc 4444).

4.6 Limitations imposed by weather conditions

4.6.1 Flight in accordance with the visual flight rules

A flight, except one of purely local character in visual meteorological conditions, to be conducted in accordance with the visual flight rules shall not be commenced unless available current meteorological reports, or a combination of current reports and forecasts, indicate that the meteorological conditions along the route, or that part of the route to be flown under the visual flight rules, will, at the appropriate time, be such as to render compliance with these rules possible.

4.6.2 Flight in accordance with the instrument flight rules

4.6.2.1 When a destination alternate aerodrome is required. A flight to be conducted in accordance with the instrument flight rules shall not be commenced unless the available information indicates that conditions, at the aerodrome of intended landing and at least one destination alternate will, at the estimated time of arrival, be at or above the aerodrome operating minima.

4.6.2.2 When no destination alternate aerodrome is required. A flight to be conducted in accordance with the instrument flight rules to an aerodrome when no alternate aerodrome is required shall not be commenced unless:

- a) a standard instrument approach procedure is prescribed for the aerodrome of intended landing; and
- b) available current meteorological information indicates that the following meteorological conditions will exist from two hours before to two hours after the estimated time of arrival:
 - 1) a cloud base of at least 300 m (1 000 ft) above the minimum associated with the instrument approach procedure; and
 - 2) visibility of at least 5.5 km or of 4 km more than the minimum associated with the procedure.

4.6.3 A flight shall not be continued towards the aerodrome of intended landing unless the latest available meteorological information indicates that conditions at that aerodrome, or at least one destination alternate aerodrome, will, at the estimated time of arrival, be at or above the specified aerodrome operating minima.

4.6.4 Except in the case of emergency, an aeroplane shall not continue its approach-to-land beyond a point at which the limits of the aerodrome operating minima would be infringed.

4.6.5 A flight to be operated in known or expected icing conditions shall not be commenced unless the aeroplane is certificated and equipped to cope with such conditions.

4.7 Destination alternate aerodromes

For a flight to be conducted in accordance with the instrument flight rules, at least one destination alternate aerodrome shall be selected and specified in the flight plan, unless:

- a) the duration of the flight and the meteorological conditions prevailing are such that there is reasonable certainty that, at the estimated time of arrival at the aerodrome of intended landing, and for a reasonable period before and after such time, the approach and landing may be made under visual meteorological conditions; or
- b) the aerodrome of intended landing is isolated and there is no suitable destination alternate aerodrome.

4.8 Fuel and oil supply

4.8.1 A flight shall not be commenced unless, taking into account both the meteorological conditions and any delays that are expected in flight, the aeroplane carries sufficient fuel and oil to ensure that it can safely complete the flight, and, as applicable, the following special provisions are complied with:

4.8.1.1 Flight in accordance with the instrument flight rules. At least sufficient fuel and oil shall be carried to allow the aeroplane:

- a) when, in accordance with the exception contained in 4.6.2.2, a destination alternate aerodrome is not required, to fly to the aerodrome to which the flight is planned and thereafter for a period of 45 minutes; or
- b) when a destination alternate aerodrome is required, to fly to the aerodrome to which the flight is planned, thence to an alternate aerodrome, and thereafter for a period of 45 minutes.

Note.— Nothing in 4.8 precludes amendment of a flight plan in flight in order to re-plan the flight to another aerodrome, provided that the requirements of 4.8 can be complied with from the point where the flight is re-planned.

4.9 Oxygen supply

The pilot-in-command shall ensure that breathing oxygen is available to crew members and passengers in sufficient

Annex 6 — Operation of Aircraft

quantities for all flights at such altitudes where a lack of oxygen might result in impairment of the faculties of crew members or harmfully affect passengers.

Note.— Guidance on the carriage and use of oxygen is given in Attachment B.

4.10 Use of oxygen

All flight crew members, when engaged in performing duties essential to the safe operation of an aeroplane in flight, shall use breathing oxygen continuously whenever the circumstances prevail for which its supply has been required in 4.9.

4.11 In-flight emergency instruction

In an emergency during flight, the pilot-in-command shall ensure that all persons on board are instructed in such emergency action as may be appropriate to the circumstances.

4.12 Weather reporting by pilots

Recommendation.— When weather conditions likely to affect the safety of other aircraft are encountered, they should be reported as soon as possible.

4.13 Hazardous flight conditions

Recommendation.— Hazardous flight conditions, other than those associated with meteorological conditions, encountered en route should be reported as soon as possible. The reports so rendered should give such details as may be pertinent to the safety of other aircraft.

4.14 Fitness of flight crew members

The pilot-in-command shall be responsible for ensuring that a flight:

- a) will not be commenced if any flight crew member is incapacitated from performing duties by any cause such as injury, sickness, fatigue, the effects of alcohol or drugs; and
- b) will not be continued beyond the nearest suitable aerodrome when flight crew members' capacity to perform functions is significantly reduced by impairment of faculties from causes such as fatigue, sickness, lack of oxygen.

4.15 Flight crew members at duty stations

4.15.1 Take-off and landing

All flight crew members required to be on flight deck duty shall be at their stations.

4.15.2 En route

All flight crew members required to be on flight deck duty shall remain at their stations except when their absence is necessary for the performance of duties in connexion with the operation of the aeroplane, or for physiological needs.

4.15.3 Seat belts

All flight crew members shall keep their seat belts fastened when at their stations.

4.15.4 Safety harness

Recommendation.— When safety harnesses are provided, any flight crew member occupying a pilot's seat should keep the safety harness fastened during the take-off and landing phases; all other flight crew members should keep their safety harnesses fastened during the take-off and landing phases unless the shoulder straps interfere with the performance of their duties, in which case the shoulder straps may be unfastened but the seat belt must remain fastened.

Note.— Safety harness includes shoulder strap(s) and a seat belt which may be used independently.

4.16 Instrument flight procedures

4.16.1 One or more instrument approach procedures designed in accordance with the classification of instrument approach and landing operations shall be approved and promulgated by the State in which the aerodrome is located to serve each instrument runway or aerodrome utilized for instrument flight operations.

4.16.2 All aeroplanes operated in accordance with instrument flight rules shall comply with the instrument flight procedures approved by the State in which the aerodrome is located.

Note I.— Definitions for the classification of instrument approach and landing operations are in Chapter 1.

Chapter 4

Note 2.— Operational procedures recommended for the guidance of operations personnel involved in instrument flight operations are described in PANS-OPS (Doc 8168), Volume I.

Note 3.— Criteria for the construction of instrument flight procedures for the guidance of procedure specialists are provided in PANS-OPS (Doc 8168), Volume II.

4.17 Instruction - general

An aeroplane shall not be taxied on the movement area of an aerodrome unless the person at the controls:

- a) has been duly authorized by the owner or in the case where it is leased the lessee, or a designated agent;
- b) is fully competent to taxi the aeroplane;
- c) is qualified to use the radio telephone if radio communications are required; and
- d) has received instruction from a competent person in respect of aerodrome layout, and where appropriate, information on routes, signs, marking, lights, ATC signals and instructions, phraseology and procedures, and is able to conform to the operational standards required for safe aeroplane movement at the aerodrome.

4.18 Refuelling with passengers on board

4.18.1 **Recommendation.**— An aeroplane should not be refuelled when passengers are embarking, on board or disembarking unless it is attended by the pilot-in-command or other qualified personnel ready to initiate and direct an evacuation of the aeroplane by the most practical and expeditious means available.

4.18.2 **Recommendation.**— When refuelling with passengers embarking, on board or disembarking, two-way communications should be maintained by aeroplane intercommunications system or other suitable means between the ground crew supervising the refuelling and the pilot-in-command or other qualified personnel required by 4.18.1.

Note 1.— The provisions of 4.18.1 do not necessarily require the deployment of integral aeroplane stairs or the opening of emergency exits as a prerequisite to refuelling.

Note 2.— Provisions concerning aircraft refuelling are contained in Annex 14, Volume I and guidance on safe refuelling practices is contained in the Airport Services Manual, Parts 1 and 8.

Note 3.— Additional precautions are required when refuelling with fuels other than aviation kerosene or when refuelling results in a mixture of aviation kerosene with other aviation turbine fuels, or when an open line is used.

CHAPTER 5. AEROPLANE PERFORMANCE OPERATING LIMITATIONS

5.1 An aeroplane shall be operated:

- a) in compliance with the terms of its airworthiness certificate or equivalent approved document;
- b) within the operating limitations prescribed by the certificating authority of the State of Registry; and
- c) within the mass limitations imposed by compliance with the applicable noise certification Standards in Annex 16, Volume I, unless otherwise authorized, in exceptional circumstances for a certain aerodrome or a runway

where there is no noise disturbance problem, by the competent authority of the State in which the aerodrome is situated.

5.2 Placards, listings, instrument markings, or combinations thereof, containing those operating limitations prescribed by the certificating authority of the State of Registry for visual presentation, shall be displayed in the aeroplane.

Note.— The Standards of Annex 8 — Airworthiness of Aircraft, Part III, apply to all aeroplanes of over 5 700 kg maximum certificated take-off mass intended for the carriage of passengers or cargo or mail in international air navigation.

CHAPTER 6. AEROPLANE INSTRUMENTS AND EQUIPMENT

Note.— Specifications for the provision of aeroplane communication and navigation equipment are contained in Chapter 7.

6.1 All aeroplanes on all flights

6.1.1 General

In addition to the minimum equipment necessary for the issuance of a certificate of airworthiness, the instruments, equipment and flight documents prescribed in the following paragraphs shall be installed or carried, as appropriate, in aeroplanes according to the aeroplane used and to the circumstances under which the flight is to be conducted.

6.1.2 Instruments

An aeroplane shall be equipped with instruments which will enable the flight crew to control the flight path of the aeroplane, carry out any required procedural manoeuvre, and observe the operating limitations of the aeroplane in the expected operating conditions.

6.1.3 Equipment

6.1.3.1 All aeroplanes on all flights.

6.1.3.1.1 All aeroplanes on all flights shall be equipped with:

- a) an accessible first-aid kit;
- b) portable fire extinguishers of a type which, when discharged, will not cause dangerous contamination of the air within the aeroplane. At least one shall be located in:
 - 1) the pilot's compartment; and
 - each passenger compartment that is separate from the pilot's compartment and not readily accessible to the pilot or co-pilot;
- c) 1) a seat or berth for each person over an age to be determined by the State of Registry; and

- 2) a seat belt for each seat and restraining belts for each berth;
- d) the following manuals, charts and information:
 - 1) the flight manual or other documents or information concerning any operating limitations prescribed for the aeroplane by the certificating authority of the State of Registry, required for the application of Chapter 5;
 - current and suitable charts for the route of the proposed flight and all routes along which it is reasonable to expect that the flight may be diverted;
 - 3) procedures, as prescribed in Annex 2, for pilots-incommand of intercepted aircraft; and
 - 4) visual signals for use by intercepting and intercepted aircraft, as contained in Annex 2; and
- e) spare electrical fuses of appropriate ratings for replacement of those accessible in flight.

6.1.3.1.2 **Recommendation.**— All aeroplanes on all flights should be equipped with the ground-air signal codes for search and rescue purposes.

6.1.3.1.3 **Recommendation.**— All aeroplanes on all flights should be equipped with a safety harness for each flight crew member seat.

Note.— Safety harness includes shoulder strap(s) and a seat belt which may be used independently.

6.1.4 Marking of break-in points

6.1.4.1 If areas of the fuselage suitable for break-in by rescue crews in an emergency are marked on an aeroplane, such areas shall be marked as shown below (see figure following). The colour of the markings shall be red or yellow, and if necessary they shall be outlined in white to contrast with the background.

6.1.4.2 If the corner markings are more than 2 m apart, intermediate lines 9 cm x 3 cm shall be inserted so that there is no more than 2 m between adjacent markings.

Note.— This Standard does not require any aeroplane to have break-in areas.

6.2 All aeroplanes operated as VFR flights

6.2.1 All aeroplanes when operated as VFR flights shall be equipped with:

a) a magnetic compass;

- b) an accurate timepiece indicating the time in hours, minutes and seconds;
- c) a sensitive pressure altimeter;
- d) an airspeed indicator; and
- e) such additional instruments or equipment as may be prescribed by the appropriate authority.

6.2.2 **Recommendation.**— VFR flights which are operated as controlled flights should be equipped in accordance with 6.6.

6.3 All aeroplanes on flights over water

6.3.1 Seaplanes

All seaplanes for all flights shall be equipped with:

a) one life jacket, or equivalent individual floatation device, for each person on board, stowed in a position readily accessible from his seat or berth;

- b) equipment for making the sound signals prescribed in the International Regulations for Preventing Collisions at Sea, where applicable;
- c) one anchor;
- d) one sea anchor (drogue), when necessary to assist in manoeuvring.

Note.— "Seaplanes" includes amphibians operated as seaplanes.

6.3.2 Landplanes

6.3.2.1 Single-engined aeroplanes.

Recommendation.— All single-engined landplanes when flying en route over water beyond gliding distance from the shore should carry one life jacket or equivalent individual floatation device for each person on board, stowed in a position easily accessible from the seat or berth of the person for whose use it is provided.

Note.— "Landplanes" includes amphibians operated as landplanes.

6.3.3 All aeroplanes on extended flights over water

All aeroplanes when operated on extended flights over water shall be equipped with:



MARKING OF BREAK-IN POINTS (see 6.1.4)

Chapter 6

- a) when the aeroplane may be over water at a distance of more than 93 km (50 NM) away from land suitable for making an emergency landing:
 - one life jacket or equivalent individual floatation device for each person on board, stowed in a position easily accessible from the seat or berth of the person for whose use it is provided;
- b) when over water away from land suitable for making an emergency landing at a distance of more than 185 km (100 NM), in the case of single-engined aeroplanes, and more than 370 km (200 NM), in the case of multi-engined aeroplanes capable of continuing flight with one engine inoperative:
 - 1) life-saving rafts in sufficient numbers to carry all persons on board, stowed so as to facilitate their ready use in emergency, provided with such lifesaving equipment including means of sustaining life as is appropriate to the flight to be undertaken; and
 - 2) equipment for making the pyrotechnical distress signals described in Annex 2.

6.4 All aeroplanes on flights over designated land areas

Aeroplanes when operated across land areas which have been designated by the State concerned as areas in which search and rescue would be especially difficult, shall be equipped with such signalling devices and life-saving equipment (including means of sustaining life) as may be appropriate to the area overflown.

6.5 All aeroplanes on high altitude flights

6.5.1 All aeroplanes intended to be operated at high altitudes shall be equipped with oxygen storage and dispensing apparatus capable of storing and dispensing the oxygen supplies required in 4.9.

6.5.2 Aeroplanes for which the individual certificate of airworthiness is first issued on or after 1 January 1990

Pressurized aeroplanes intended to be operated at flight altitudes at which the atmospheric pressure is less than 376 hPa shall be equipped with a device to provide positive warning to the flight crew of any dangerous loss of pressurization. 6.5.3 Aeroplanes for which the individual certificate of airworthiness is first issued before 1 January 1990

Recommendation.— Pressurized aeroplanes intended to be operated at flight altitudes at which the atmospheric pressure is less than 376 hPa should be equipped with a device to provide positive warning to the flight crew of any dangerous loss of pressurization.

6.6 All aeroplanes operated in accordance with the instrument flight rules

All aeroplanes when operated in accordance with the instrument flight rules or when the aeroplane cannot be maintained in a desired attitude without reference to one or more flight instruments, shall be equipped with:

- a) a magnetic compass;
- b) an accurate timepiece indicating the time in hours, minutes and seconds;
- c) a sensitive pressure altimeter;

Note.— Due to the long history of misreadings, the use of drum-pointer altimeters is not recommended.

- d) an airspeed indicating system with a means of preventing malfunctioning due to either condensation or icing;
- e) a turn and slip indicator;
- f) an attitude indicator (artificial horizon);
- g) a heading indicator (directional gyroscope);

Note.— The requirements of e), f) and g) above, may be met by combinations of instruments or by integrated flight director systems provided that the safeguards against total failure, inherent in the three separate instruments, are retained.

- h) means of indicating whether the supply of power to the gyroscopic instruments is adequate;
- i) a means of indicating in the flight crew compartment the outside air temperature;
- j) a rate-of-climb and descent indicator; and
- k) such additional instruments or equipment as may be prescribed by the appropriate authority.

6.7 All aeroplanes when operated at night

All aeroplanes, when operated at night, shall be equipped with:

.

Annex 6 — Operation of Aircraft

b) the lights required by Annex 2 for aircraft in flight or operating on the movement area of an aerodrome;

Note.— Specifications for lights meeting the requirements of Annex 2 for navigation lights are contained in the Appendix. The general characteristics of lights are specified in Annex 8. Detailed specifications for lights meeting the requirements of Annex 2 for aircraft in flight or operating on the movement area of an aerodrome are contained in the Airworthiness Technical Manual (Doc 9051).

- c) a landing light;
- d) illumination for all flight instruments and equipment that are essential for the safe operation of the aeroplane;
- e) lights in all passenger compartments; and
- f) an electric torch for each crew member station.

6.8 All aeroplanes complying with the noise certification Standards in Annex 16, Volume I

An aeroplane shall carry a document attesting noise certification.

Note.— The attestation may be contained in any document, carried on board, approved by the State of Registry.

6.9 Aeroplanes required to be equipped with ground proximity warning systems (GPWS)

6.9.1 **Recommendation.**— All turbine-engined aeroplanes of a maximum certificated take-off mass in excess of 15 000 kg or authorized to carry more than 30 passengers should be equipped with a ground proximity warning system.

6.9.2 All turbine-engined aeroplanes of a maximum certificated take-off mass in excess of 5 700 kg or authorized to carry more than nine passengers shall be equipped with a ground proximity warning system from 1 January 1999.

6.9.3 A ground proximity warning system shall provide automatically a timely and distinctive warning to the flight crew when the aeroplane is in potentially hazardous proximity to the earth's surface.

6.9.4 From 1 January 1999 a ground proximity warning system shall provide, as a minimum, warnings of the following circumstances;

1) excessive descent rate;

- 3) excessive altitude loss after take-off or go-around;
- unsafe terrain clearance while not in landing configuration;
 - a) gear not locked down;
 - b) flaps not in a landing position; and
- 5) excessive descent below the instrument glide path.

6.9.5 **Recommendation.**— All piston-engined aeroplanes of a maximum certificated take-off mass in excess of 5 700 kg or authorized to carry more than nine passengers should be equipped with a ground proximity warning system.

6.10 Flight recorders

Note 1.— Flight recorders comprise two systems, a flight data recorder and a cockpit voice recorder.

Note 2.— Combination recorders (FDR/CVR) can only be used to meet the flight recorder equipage requirements as specifically indicated in this Annex.

Note 3.— Detailed guidance on flight recorders is contained in Attachment A.

6.10.1 Flight data recorders - types

6.10.1.1 A Type I flight data recorder shall record the parameters required to determine accurately the aeroplane flight path, speed, attitude, engine power, configuration and operation.

6.10.1.2 A Type II flight data recorder shall record the parameters required to determine accurately the aeroplane flight path, speed, attitude, engine power and configuration of lift and drag devices.

6.10.1.3 The use of engraving metal foil flight data recorders shall be discontinued by 1 January 1995.

6.10.1.4 **Recommendation.**— The use of photographic film data recorders and analogue data recorders using frequency modulation (FM) should be discontinued by 5 November 1998.

6.10.1.5 All aeroplanes equipped to utilize digital communications and required to carry a cockpit voice recorder shall record on the cockpit voice recorder or the flight data recorder the digital communications with ATS.

6.10.1.5.1 If recorded on the flight data recorder, the digital communications shall be readily correlatable to the cockpit voice recording.

Chapter 6

6.10.1.6 **Recommendation**.— All aeroplanes of a maximum certificated take-off mass over 5 700 kg, required to be equipped with a flight data recorder and a cockpit voice recorder, may alternatively be equipped with two combination recorders (FDR/CVR).

6.10.2 Flight data recorders - duration

Types I and II flight data recorders shall be capable of retaining the information recorded during at least the last 25 hours of their operation.

6.10.3 Flight data recorders — aeroplanes for which the individual certificate of airworthiness is first issued on or after 1 January 1989

6.10.3.1 All aeroplanes of a maximum certificated takeoff mass of over 27 000 kg shall be equipped with a Type I flight data recorder.

6.10.3.2 **Recommendation.**— All aeroplanes of a maximum certificated take-off mass of over 5 700 kg up to and including 27 000 kg should be equipped with a Type II flight data recorder.

6.10.4 Cockpit voice recorders — aeroplanes for which the individual certificate of airworthiness is first issued on or after 1 January 1987

6.10.4.1 All aeroplanes of a maximum certificated takeoff mass of over 27 000 kg shall be equipped with a cockpit voice recorder, the objective of which is the recording of the aural environment on the flight deck during flight time.

6.10.4.2 **Recommendation.** All aeroplanes of a maximum certificated take-off mass of over 5 700 kg up to and including 27 000 kg should be equipped with a cockpit voice recorder, the objective of which is the recording of the aural environment on the flight deck during flight time.

6.10.5 Cockpit voice recorders — duration

6.10.5.1 A cockpit voice recorder shall be capable of retaining the information recorded during at least the last 30 minutes of its operation.

6.10.5.2 **Recommendation.**— A cockpit voice recorder, installed in aeroplanes of a maximum certificated take-off mass of over 5 700 kg for which the individual certificate of airworthiness is first issued on or after 1 January 1990, should be capable of retaining the information recorded during at least the last two hours of its operation.

6.10.6 Flight recorders — construction and installation

Flight recorders shall be constructed, located and installed so as to provide maximum practical protection for the recordings in order that the recorded information may be preserved, recovered and transcribed. Flight recorders shall meet the prescribed crashworthiness and fire protection specifications.

Note.— Industry crashworthiness and fire protection specifications can be found in documents such as the European Organization for Civil Aviation Electronics (EUROCAE) documents ED55 and ED56A.

6.10.7 Flight recorders - operation

6.10.7.1 Flight recorders shall not be switched off during flight time.

6.10.7.2 To preserve flight recorder records, flight recorders shall be de-activated upon completion of flight time following an accident or incident. The flight recorders shall not be re-activated before their disposition as determined in accordance with Annex 13.

Note 1.— The need for removal of the flight recorder records from the aircraft will be determined by the investigation authority in the State conducting the investigation with due regard to the seriousness of an occurrence and the circumstances, including the impact on the operation.

Note 2.— The pilot-in-command's responsibilities regarding the retention of flight recorder records are contained in 6.10.8.

6.10.8 Flight recorder records

The pilot-in-command shall ensure, to the extent possible, in the event the aeroplane becomes involved in an accident or incident, the preservation of all related flight recorder records, and if necessary the associated flight recorders, and their retention in safe custody pending their disposition as determined in accordance with Annex 13.

6.10.9 Flight recorders — continued serviceability

Operational checks and evaluations of recordings from the flight data and cockpit voice recorder systems shall be conducted to ensure the continued serviceability of the recorders.

Note.— Procedures for the inspections of the flight data and cockpit voice recorder systems are given in Attachment A.

6.11 Mach number indicator

All aeroplanes with speed limitations expressed in terms of Mach number shall be equipped with a Mach number indicator.

Note.— This does not preclude the use of the airspeed indicator to derive Mach number for ATS purposes.

6.12 Emergency locator transmitter (ELT)

6.12.1 All aeroplanes operated on extended flights over water as described in 6.3.3 b) and when operated on flights over designated land areas as described in 6.4 shall be equipped with one ELT.

6.12.2 **Recommendation.**— All aeroplanes should carry an automatically activated ELT.

6.12.3 ELT equipment carried to satisfy the requirements of 6.12.1 and 6.12.2 shall operate in accordance with the relevant provisions of Annex 10, Volume III.

6.13 Aeroplanes required to be equipped with a pressure-altitude reporting transponder

To fly in designated airspaces, all aeroplanes shall be equipped with a pressure-altitude reporting transponder which operates in accordance with the relevant provisions of Annex 10, Volume IV.

Note.— This provision is intended to improve the effectiveness of air traffic services as well as airborne collision avoidance systems.

6.14 Microphones

Recommendation.— All flight crew members required to be on flight deck duty should communicate through boom or throat microphones below the transition level/altitude.

CHAPTER 7. AEROPLANE COMMUNICATION AND NAVIGATION EQUIPMENT

7.1 Communication equipment

7.1.1 An aeroplane to be operated in accordance with the instrument flight rules or at night shall be provided with radio communication equipment. Such equipment shall be capable of conducting two-way communication with those aeronautical stations and on those frequencies prescribed by the appropriate authority.

Note.— The requirements of 7.1.1 are considered fulfilled if the ability to conduct the communications specified therein is established during radio propagation conditions which are normal for the route.

7.1.2 When compliance with 7.1.1 requires that more than one communications equipment unit be provided, each shall be independent of the other or others to the extent that a failure in any one will not result in failure of any other.

7.1.3 An aeroplane to be operated in accordance with the visual flight rules, but as a controlled flight, shall, unless exempted by the appropriate authority, be provided with radio communication equipment capable of conducting two-way communication at any time during flight with such aeronautical stations and on such frequencies as may be prescribed by the appropriate authority.

7.1.4 An aeroplane to be operated on a flight to which the provisions of 6.3.3 or 6.4 apply shall, unless exempted by the appropriate authority, be provided with radio communication equipment capable of conducting two-way communication at any time during flight with such aeronautical stations and on such frequencies as may be prescribed by the appropriate authority.

7.1.5 The radio communication equipment required in accordance with 7.1.1 to 7.1.4 shall provide for communication on the aeronautical emergency frequency 121.5 MHz.

7.2 Navigation equipment

7.2.1 An aeroplane shall be provided with navigation equipment which will enable it to proceed:

- a) in accordance with the flight plan;
- b) in accordance with prescribed RNP types; and
- c) in accordance with the requirements of air traffic services;

except when, if not so precluded by the appropriate authority, navigation for flights under the visual flight rules is accomplished by visual reference to landmarks at least every 110 km (60 NM).

Note.— Information on RNP and associated procedures is contained in the Manual on Required Navigation Performance (RNP) (Doc 9613).

7.2.2 For flights in defined portions of airspace where, based on Regional Air Navigation Agreement, minimum navigation performance specifications (MNPS) are prescribed, an aeroplane shall be provided with navigation equipment which:

- a) continuously provides indications to the flight crew of adherence to or departure from track to the required degree of accuracy at any point along that track; and
- b) has been authorized by the State of Registry for MNPS operations concerned.

Note.— The prescribed minimum navigation performance specifications and the procedures governing their application are published in Regional Supplementary Procedures (Doc 7030).

7.2.3 For flights in defined portions of airspace where, based on Regional Air Navigation Agreement, a vertical separation minimum (VSM) of 300 m (1 000 ft) is applied above FL 290, an aeroplane:

- a) shall be provided with equipment which is capable of:
 - 1) indicating to the flight crew the flight level being flown;
 - 2) automatically maintaining a selected flight level;
 - 3) providing an alert to the flight crew when a deviation occurs from the selected flight level. The threshold for the alert shall not exceed ± 90 m (300 ft); and
 - 4) automatically reporting pressure-altitude; and
- b) shall be authorized by the State of Registry for operation in the airspace concerned.

7.2.4 The aeroplane shall be sufficiently provided with navigation equipment to ensure that, in the event of the failure of one item of equipment at any stage of the flight, the remaining equipment will enable the aeroplane to proceed in accordance with 7.2.1 and where applicable 7.2.2 and 7.2.3.

Note 1.— This requirement may be met by means other than the duplication of equipment.

Note 2.— Guidance material relating to aircraft equipment necessary for flight in airspace where a 300 m (1 000 ft) VSM is applied above FL 290 is contained in the Manual on Implementation of a 300 m (1 000 ft) Vertical Separation Minimum Between FL 290 and FL 410 Inclusive (Doc 9574). 7.2.5 On flights in which it is intended to land in instrument meteorological conditions, an aeroplane shall be provided with radio equipment capable of receiving signals providing guidance to a point from which a visual landing can be effected. This equipment shall be capable of providing such guidance for each aerodrome at which it is intended to land in instrument meteorological conditions and for any designated alternate aerodromes.

CHAPTER 8. AEROPLANE MAINTENANCE

Note on the application of this Chapter.— For the purpose of this Chapter "aeroplane" includes: powerplants, propellers, components, accessories, instruments, equipment and apparatus including emergency equipment.

8.1 Responsibility

8.1.1 The owner of an aeroplane, or in the case where it is leased, the lessee, shall be responsible for its maintenance in an airworthy condition when in use.

8.1.2 The owner of an aeroplane, or in the case where it is leased, the lessee, shall be responsible for ensuring, in so far as practicable, that:

- a) all maintenance, overhaul, alterations and repairs which affect airworthiness, are performed as prescribed by the State of Registry;
- b) maintenance personnel make appropriate entries in the aeroplane maintenance records certifying that the aeroplane is airworthy;
- c) the maintenance release is completed and signed by a person or persons qualified in accordance with the provisions of Annex 1 to certify that the maintenance work has been completed satisfactorily and in accordance with the prescribed methods.

8.2 Qualification to certify as airworthy

Each person charged with the responsibility of certifying as to the airworthiness of an aeroplane shall be qualified in accordance with the provisions of Annex 1.

8.3 Maintenance records

8.3.1 The owner of an aeroplane shall keep a maintenance record of the following:

- a) In respect of the entire aeroplane:
 - 1) the current empty mass and the location of the centre of gravity when empty;
 - 2) the addition or removal of equipment;
 - the kind and extent of the maintenance and alteration and the time in service and date when the work was performed;
 - 4) chronological list of compliance with airworthiness directives and the methods of compliance.
- b) In respect of the major components:
 - 1) the total time in service;
 - 2) the date of the last overhaul;
 - 3) the time in service since the last overhaul;
 - 4) the date of the last inspection.
- c) In respect of those instruments and equipment, the serviceability and operating life of which are determined by their time in service:
 - such records of the time in service as are necessary to determine their serviceability or to compute their operating life;
 - 2) the date of the last inspection.

8.3.2 The records referred to in 8.3.1 shall be kept for a period of 90 days after the end of the operating life of the unit to which they refer.

8.3.3 The lessee of an aeroplane shall comply with the requirements of 8.3.1 and 8.3.2, as applicable, while the aeroplane is leased.

Note.— Maintenance records or related documents, other than a valid certificate of airworthiness, need not be carried in the aeroplane during international flights.

CHAPTER 9. AEROPLANE FLIGHT CREW

9.1 Qualifications

The pilot-in-command shall ensure that the licences of each flight crew member have been issued or rendered valid by the State of Registry, and are properly rated and of current validity, and shall be satisfied that flight crew members have maintained competence.

9.2 Composition of the flight crew

The number and composition of the flight crew shall not be less than that specified in the flight manual or other documents associated with the certificate of airworthiness.

APPENDIX. LIGHTS TO BE DISPLAYED BY AEROPLANES

(Note.— See Chapter 6)

1. Terminology

When the following terms are used in this Appendix, they have the following meanings:

Angles of coverage.

- a) Angle of coverage A is formed by two intersecting vertical planes making angles of 70 degrees to the right and 70 degrees to the left respectively, looking aft along the longitudinal axis to a vertical plane passing through the longitudinal axis.
- b) Angle of coverage F is formed by two intersecting vertical planes making angles of 110 degrees to the right and 110 degrees to the left respectively, looking forward along the longitudinal axis to a vertical plane passing through the longitudinal axis.
- c) Angle of coverage L is formed by two intersecting vertical planes, one parallel to the longitudinal axis of the aeroplane, and the other 110 degrees to the left of the first, when looking forward along the longitudinal axis.
- d) Angle of coverage R is formed by two intersecting vertical planes, one parallel to the longitudinal axis of the aeroplane, and the other 110 degrees to the right of the first, when looking forward along the longitudinal axis.
- Horizontal plane. The plane containing the longitudinal axis and perpendicular to the plane of symmetry of the aeroplane.
- **Longitudinal axis of the aeroplane.** A selected axis parallel to the direction of flight at a normal cruising speed, and passing through the centre of gravity of the aeroplane.
- Making way. An aeroplane on the surface of the water is "making way" when it is under way and has a velocity relative to the water.
- **Under command.** An aeroplane on the surface of the water is "under command" when it is able to execute manoeuvres as required by the International Regulations for Preventing Collisions at Sea for the purpose of avoiding other vessels.
- **Under way.** An aeroplane on the surface of the water is "under way" when it is not aground or moored to the ground or to any fixed object on the land or in the water.

Vertical planes. Planes perpendicular to the horizontal plane.

Visible. Visible on a dark night with a clear atmosphere.

2. Navigation lights to be displayed in the air

Note.— The lights specified herein are intended to meet the requirements of Annex 2 for navigation lights.

As illustrated in Figure 1, the following unobstructed navigation lights shall be displayed:



- a) a red light projected above and below the horizontal plane through angle of coverage L;
- b) a green light projected above and below the horizontal plane through angle of coverage R;
- c) a white light projected above and below the horizontal plane rearward through angle of coverage A.

3. Lights to be displayed on the water

3.1 General

Note.— The lights specified herein are intended to meet the . requirements of Annex 2 for lights to be displayed by aeroplanes on the water.

The International Regulations for Preventing Collisions at Sea require different lights to be displayed in each of the following circumstances:

a) when under way;

- b) when towing another vessel or aeroplane;
- c) when being towed;
- d) when not under command and not making way;
- e) when making way but not under command;
- f) when at anchor;
- g) when aground.

The lights required by aeroplanes in each case are described below.

3.2 When under way

As illustrated in Figure 2, the following appearing as steady unobstructed lights:

- a) a red light projected above and below the horizontal through angle of coverage L;
- b) a green light projected above and below the horizontal through angle of coverage R;
- c) a white light projected above and below the horizontal through angle of coverage A; and
- d) a white light projected through angle of coverage F.

The lights described in a), b) and c) should be visible at a distance of at least 3.7 km (2 NM). The light described in d) should be visible at a distance of 9.3 km (5 NM) when fitted to an aeroplane of 20 m or more in length or visible at a distance of 5.6 km (3 NM) when fitted to an aeroplane of less than 20 m in length.



3.3 When towing another vessel or aeroplane

As illustrated in Figure 3, the following appearing as steady, unobstructed lights:

a) the lights described in 3.2 above;

- b) a second light having the same characteristics as the light described in 3.2 d) and mounted in a vertical line at least 2 m above or below it; and
- c) a yellow light having otherwise the same characteristics as the light described in 3.2 c) and mounted in a vertical line at least 2 m above it.



3.4 When being towed

The lights described in 3.2 a), b) and c) appearing as steady, unobstructed lights.

3.5 When not under command and not making way

As illustrated in Figure 4, two steady red lights placed where they can best be seen, one vertically over the other and not less than 1 m apart, and of such a character as to be visible all around the horizon at a distance of at least 3.7 km (2 NM).



3.6 When making way but not under command

As illustrated in Figure 5, the lights described in 3.5 plus the lights described in 3.2 a), b) and c).

Note.— The display of lights prescribed in 3.5 and 3.6 above is to be taken by other aircraft as signals that the aeroplane showing them is not under command and cannot therefore get out of the way. They are not signals of aero-planes in distress and requiring assistance.



3.7 When at anchor

- a) If less than 50 m in length, where it can best be seen, a steady white light (Figure 6), visible all around the horizon at a distance of at least 3.7 km (2 NM).
- b) If 50 m or more in length, where they can best be seen, a steady white forward light and a steady white rear light (Figure 7) both visible all around the horizon at a distance of at least 5.6 km (3 NM).
- c) If 50 m or more in span a steady white light on each side (Figures 8 and 9) to indicate the maximum span and visible, so far as practicable, all around the horizon at a distance of at least 1.9 km (1 NM).









3.8 When aground

The lights prescribed in 3.7 and in addition two steady red lights in vertical line, at least 1 m apart so placed as to be visible all around the horizon.

THIS PAGE INTENTIONALLY LEFT BLANK

Supplementary to 6.10

Introduction

The material in this Attachment concerns flight recorders intended for installation in aeroplanes engaged in international air navigation. Flight recorders comprise two systems — a flight data recorder and a cockpit voice recorder. Flight data recorders are classified as Type I and Type II depending upon the number of parameters to be recorded.

1. Flight data recorder (FDR)

1.1 General requirements

1.1.1 The recorder is to record continuously during flight time.

- 1.1.2 The recorder container is to:
- a) be painted a distinctive orange or yellow colour;
- b) carry reflective material to facilitate its location; and
- c) have securely attached an automatically activated underwater locating device.
- 1.1.3 The recorder is to be installed so that:
- a) the probability of damage to the recording is minimized. To meet this requirement it should be located as far aft as practicable. In the case of pressurized aeroplanes it should be located in the vicinity of the rear pressure bulkhead;
- b) it receives its electrical power from a bus that provides the maximum reliability for operation of the recorder without jeopardizing service to essential or emergency loads; and
- c) there is an aural or visual means for pre-flight checking that the recorder is operating properly.

1.2 Parameters to be recorded

1.2.1 Type I flight data recorder. This recorder will be capable of recording, as appropriate to the aeroplane, at least

the 32 parameters in Table A-1. However, other parameters may be substituted with due regard to the aeroplane type and the characteristics of the recording equipment.

1.2.2 Type II flight data recorder. This recorder will be capable of recording, as appropriate to the aeroplane, at least the first 15 parameters in Table A-1. However, other parameters may be substituted with due regard to the aeroplane type and the characteristics of the recording equipment.

1.3 Additional information

1.3.1 The measurement range, recording interval and accuracy of parameters on installed equipment is usually verified by methods approved by the appropriate certificating authority.

1.3.2 The manufacturer usually provides the national certificating authority with the following information in respect of the flight data recorder:

- a) manufacturer's operating instructions, equipment limitations and installation procedures;
- b) parameter origin or source and equations which relate counts to units of measurement; and
- c) manufacturer's test reports.

1.3.3 The operator usually supplies position error curves for pitot-static parameters, at various angles of attack and side slip, for the calibration and read-out of the recordings.

- 2. Cockpit voice recorder (CVR)
 - 2.1 General requirements

2.1.1 The recorder is to be designed so that it will record at least the following:

- a) voice communication transmitted from or received in the aeroplane by radio;
- b) aural environment on the flight deck;
- c) voice communication of flight crew members on the flight deck using the aeroplane's interphone system;

Annex 6 — Operation of Aircraft

- d) voice or audio signals identifying navigation or approach aids introduced in the headset or speaker;
- e) voice communication of flight crew members using the passenger address system, if installed; and
- f) digital communications with ATS, unless recorded by the flight data recorder,
- 2.1.2 The recorder container is to:
- a) be painted a distinctive orange or yellow colour;
- b) carry reflective material to facilitate its location; and
- c) have securely attached an automatically activated underwater locating device.

2.1.3 To aid in voice and sound discrimination, microphones in the cockpit are to be located in the best position for recording voice communications originating at the pilot and co-pilot stations and voice communications of other crew members on the flight deck when directed to those stations. This can best be achieved by wiring suitable boom microphones to record continuously on separate channels.

2.1.4 The recorder is to be installed so that:

- a) the probability of damage to the recording is minimized. To meet this requirement it should be located as far aft as practicable. In the case of pressurized aeroplanes it should be located in the vicinity of the rear pressure bulkhead;
- b) it receives its electrical power from a bus that provides the maximum reliability for operation of the recorder without jeopardizing service to essential or emergency loads;
- c) there is an aural or visual means for pre-flight checking of the recorder for proper operation; and
- d) if the recorder has a bulk erasure device, the installation should be designed to prevent operation of the device during flight time or crash impact.
 - 2.2 Performance requirements

2.2.1 The recorder will be capable of recording on at least four tracks simultaneously. To ensure accurate time correlation between tracks, the recorder is to record in an in-line format. If a bi-directional configuration is used, the in-line format and track allocation should be retained in both directions.

- 2.2.2 The preferred track allocation is as follows:
- Track 1 co-pilot headphones and live boom microphone

Track 2 - pilot headphones and live boom microphone

Track 3 — area microphone

Track 4 — time reference plus the third and fourth crew member's headphone and live microphone, if applicable.

Note 1.— Track I is located closest to the base of the recording head.

Note 2.— The preferred track allocation presumes use of current conventional magnetic tape transport mechanisms, and is specified because the outer edges of the tape have a higher risk of damage than the middle. It is not intended to preclude use of alternative recording media where such constraints may not apply.

2.2.3 The recorder, when tested by methods approved by the appropriate certificating authority, will be demonstrated to be suitable for the environmental extremes over which it is designed to operate.

2.2.4 Means will be provided for an accurate time correlation between the flight data recorder and the cockpit voice recorder.

Note.— One method of achieving this is by superimposing the FDR time signal on the CVR.

2.3 Additional information

2.3.1 The manufacturer usually provides the national certificating authority with the following information in respect of the cockpit voice recorder:

- a) manufacturer's operating instructions, equipment limitations and installation procedures; and
- b) manufacturer's test reports.

3. Inspections of flight data and cockpit voice recorder systems

3.1 Prior to the first flight of the day, the built-in test features on the flight deck for the CVR, FDR and Flight Data Acquisition Unit (FDAU), when installed, should be monitored.

- 3.2 Annual inspections should be carried out as follows:
- a) the readout of the recorded data from the FDR and CVR should ensure that the recorder operates correctly for the nominal duration of the recording;

Attachment A

- b) the analysis of the FDR should evaluate the quality of the recorded data to determine if the bit error rate is within acceptable limits and to determine the nature and distribution of the errors;
- c) a complete flight from the FDR should be examined in engineering units to evaluate the validity of all recorded parameters. Particular attention should be given to parameters from sensors dedicated to the FDR. Parameters taken from the aircraft's electrical bus system need not be checked if their serviceability can be detected by other aircraft systems;
- d) the readout facility should have the necessary software to accurately convert the recorded values to engineering units and to determine the status of discrete signals;
- e) an annual examination of the recorded signal on the CVR should be carried out by replay of the CVR recording. While installed in the aircraft the CVR should record test signals from each aircraft source and from relevant external sources to ensure that all required signals meet intelligibility standards; and
- f) where practicable, during the annual examination, a sample of in-flight recordings of the CVR should be

examined for evidence that the intelligibility of the signal is acceptable.

3.3 Flight recorder systems should be considered unserviceable if there is a significant period of poor quality data, unintelligible signals, or if one or more of the mandatory parameters is not recorded correctly.

3.4 A report of the annual inspection should be made available on request to the State's regulatory authority for monitoring purposes.

- 3.5 Calibration of the FDR system:
- a) the FDR system should be re-calibrated at least every five years to determine any discrepancies in the engineering conversion routines for the mandatory parameters, and to ensure that parameters are being recorded within the calibration tolerances; and
- b) when the parameters of altitude and airspeed are provided by sensors that are dedicated to the FDR system, there should be a re-calibration performed as recommended by the sensor manufacturer, or at least every two years.

Table A-1 Parameters for Flight Data Recorders

Serial number	Parameter	Measurement range	Recording interval (seconds)	Accuracy limits (sensor input compared to FDR read-out)			
1	Time (UTC when available, otherwise elapsed time)	24 hours	4	±0.125% per hour			
2	Pressure-altitude	-300 m (-1 000 ft) to maximum certificated altitude of aircraft +1 500 m (+5 000 ft)	1	±30 m to ±200 m (±100 ft to ±700 ft)			
3	Indicated airspeed	95 km/h (50 kt) to max V _{S0} (<i>Note 1</i>) V _{S0} to 1.2 V _D (<i>Note 2</i>)	1	±5% ±3%			
4	Heading	360°	1	<u>+2</u> °			
5	Normal acceleration	-3 g to +6 g	0.125	$\pm 1\%$ of maximum range excluding datum error of $\pm 5\%$			
6	Pitch attitude	±75°	1	±2°			
7	Roll attitude	±180°	1	±2°			
8	Radio transmission keying	On-off (one discrete)	1				
9	Power on each engine (Note 3)	Full range	1 (per engine)	±2%			
10 .	Trailing edge flap or cockpit control selection	Full range or each discrete position	2	±5% or as pilot's indicator			
11	Leading edge flap or cockpit control selection	Full range or each discrete position	2	$\pm 5\%$ or as pilot's indicator			
12	Thrust reverser position	Stowed, in transit, and reverse	l (per engine)				
13	Ground spoiler/speed brake selection	Full range or each discrete position	1	±2% unless higher accuracy uniquely required			
14	Outside air temperature	Sensor range	2	±2℃			
15	Autopilot/auto throttle/AFCS mode and engagement status	A suitable combination of discretes	1	•			
Note.— The preceding 15 parameters satisfy the requirements for a Type II FDR.							
16	Longitudinal acceleration	±1 g	0.25	$\pm 1.5\%$ max range excluding datum error of $\pm 5\%$			
17	Lateral acceleration	±1 g	0.25	$\pm 1.5\%$ max range excluding datum error of $\pm 5\%$			

 18
 Pilot input and/or control surface position-primary controls (pitch, roll, yaw)
 Full range
 1
 ±2° unless higher accuracy uniquely required

 18
 Pilot input and/or control surface position-primary controls (pitch, roll, yaw)
 Full range
 1
 ±2° unless higher accuracy uniquely required

Annex 6 — Operation of Aircraft

Serial number	Parameter	Measurement range	Recording interval (seconds)	Accuracy limits (sensor input compared to FDR read-out)
19	Pitch trim position	Full range	1	±3% unless higher accuracy uniquely required
20	Radio altitude	6 m to 750 m (20 ft to 2 500 ft)	1	± 0.6 m (± 2 ft) or $\pm 3\%$ whichever is greater below 150 m (500 ft) and $\pm 5\%$ above 150 m (500 ft)
21	Glide path deviation	Signal range	1	±3%
22	Localizer deviation	Signal range	1	±3%
23	Marker beacon passage	Discrete	1	
24	Master warning	Discrete	1	
25	NAV 1 and 2 frequency selection (Note 5)	Full range	4	As installed
26	DME 1 and 2 distance (Notes 5 and 6)	0 – 370 km	4	As installed
27	Landing gear squat switch status	Discrete	1	
28	GPWS (ground proximity warning system)	Discrete	1	
29	Angle of attack	Full range	0.5	As installed
30	Hydraulics, each system (low pressure)	Discrete	2	
31	Navigation data (latitude/longitude, ground speed and drift angle) (Note 7)	As installed	1	As installed
32	Landing gear or gear selector position	Discrete	4	As installed

Note.--- The preceding 32 parameters satisfy the requirements for a Type 1 FDR.

Notes.—

1. V_{S_0} stalling speed or minimum steady flight speed in the landing configuration.

2. V_D design diving speed.

3. Record sufficient inputs to determine power.

4. For aeroplanes with conventional control systems "or" applies. For aeroplanes with non-mechanical control systems "and" applies. In aeroplanes with split surfaces, a suitable combination of inputs is acceptable in lieu of recording each surface separately.

5. If signal available in digital form.

6. Recording of latitude and longitude from INS or other navigation system is a preferred alternative.

7. If signals readily available,

Annex 6 - Operation of Aircraft

If further recording capacity is available, recording of the following additional information should be considered:

- a) operational information from electronic display systems, such as electronic flight instrument systems (EFIS), electronic centralized aircraft monitor (ECAM) and engine indication and crew alerting system (EICAS). Use the following order of priority:
 - 1) parameters selected by the flight crew relating to the desired flight path, e.g. barometric pressure setting, selected altitude, selected airspeed, decision height, and autoflight system engagement and mode indications if not recorded from another source;

2) display system selection/status, e.g. SECTOR, PLAN, ROSE, NAV, WXR, COMPOSITE, COPY, ETC.;

3) warnings and alerts;

4) the identity of displayed pages for emergency procedures and checklists;

b) retardation information including brake application for use in the investigation of landing overruns and rejected take-offs; and

c) additional engine parameters (EPR, N1, EGT, fuel flow, etc.).

ATTACHMENT B. CARRIAGE AND USE OF OXYGEN

Supplementary to 4.9

Introduction

The performance of crew members and the well-being of passengers during flights at such altitudes where a lack of oxygen might result in impairment of faculties are of major concern. Research conducted in altitude chambers or by exposure to mountain elevations indicates that human tolerance could be related to the altitude concerned and the exposure time. The subject is dealt with in detail in the *Manual of Civil Aviation Medicine* (Doc 8984). In the light of the above and to further assist the pilot-in-command in providing the oxygen supply intended by 4.9, the following guidelines, which take into account the requirements already established in Annex 6, Part I, are considered relevant.

1. Oxygen supply

1.1 A flight to be operated at altitudes at which the atmospheric pressure in personnel compartments will be less than 700 hPa should not be commenced unless sufficient stored breathing oxygen is carried to supply:

- a) all crew members and at least 10 per cent of the passengers for any period in excess of 30 minutes that the pressure in compartments occupied by them will be between 700 hPa and 620 hPa; and
- b) all crew members and passengers for any period that the atmospheric pressure in compartments occupied by them will be less than 620 hPa.

1.2 A flight to be operated with a pressurized aeroplane should not be commenced unless a sufficient quantity of stored breathing oxygen is carried to supply all crew members and passengers, as is appropriate to the circumstances of the flight being undertaken, in the event of loss of pressurization, for any period that the atmospheric pressure in any compartment occupied by them would be less than 700 hPa. In addition, when an aeroplane is operated at flight altitudes at which the atmospheric pressure is less than 376 hPa, or which, if operated at flight altitudes at which the atmospheric pressure is more than 376 hPa and cannot descend safely within four minutes to a flight altitude at which the atmospheric pressure is equal to 620 hPa, there shall be no less than a 10-minute supply for the occupants of the passenger compartment.

2. Use of oxygen

2.1 All flight crew members, when engaged in performing duties essential to the safe operation of an aeroplane in flight, should use breathing oxygen continuously whenever the circumstances prevail for which its supply has been indicated to be necessary in 1.1 or 1.2.

2.2 All flight crew members of pressurized aeroplanes operating above an altitude where the atmospheric pressure is less than 376 hPa should have available at the flight duty station a quick donning type of mask which will readily supply oxygen upon demand.

Note.— Approximate altitudes in the Standard Atmosphere corresponding to the values of absolute pressure used in the text are as follows:

Absolute pressure	Metres	Feet	
700 hPa	3 000	10 000	
620 hPa	4 000	13 000	
376 hPa	7 600	25 000	

— END —

ICAO TECHNICAL PUBLICATIONS

The following summary gives the status, and also describes in general terms the contents of the various series of technical publications issued by the International Civil Aviation Organization. It does not include specialized publications that do not fall specifically within one of the series, such as the Aeronautical Chart Catalogue or the Meteorological Tables for International Air Navigation.

International Standards and Recommended Practices are adopted by the Council in accordance with Articles 54, 37 and 90 of the Convention on International Civil Aviation and are designated, for convenience, as Annexes to the Convention. The uniform application by Contracting States of the specifications contained in the International Standards is recognized as necessary for the safety or regularity of international air navigation while the uniform application of the specifications in the Recommended Practices is regarded as desirable in the interest of safety, regularity or efficiency of international air navigation. Knowledge of any differences between the national regulations or practices of a State and those established by an International Standard is essential to the safety or regularity of international air navigation. In the event of non-compliance with an International Standard, a State has, in fact, an obligation, under Article 38 of the Convention, to notify the Council of any differences. Knowledge of differences from Recommended Practices may also be important for the safety of air navigation and, although the Convention does not impose any obligation with regard thereto, the Council has invited Contracting States to notify such differences in addition to those relating to International Standards.

Procedures for Air Navigation Services (PANS) are approved by the Council for world-wide application. They contain, for the most part, operating procedures regarded as not yet having attained a sufficient degree of

maturity for adoption as International Standards and Recommended Practices, as well as material of a more permanent character which is considered too detailed for incorporation in an Annex, or is susceptible to frequent amendment, for which the processes of the Convention would be too cumbersome.

Regional Supplementary Procedures (SUPPS) have a status similar to that of PANS in that they are approved by the Council, but only for application in the respective regions. They are prepared in consolidated form, since certain of the procedures apply to overlapping regions or are common to two or more regions.

The following publications are prepared by authority of the Secretary General in accordance with the principles and policies approved by the Council.

Technical Manuals provide guidance and information in amplification of the International Standards, Recommended Practices and PANS, the implementation of which they are designed to facilitate.

Air Navigation Plans detail requirements for facilities and services for international air navigation in the respective ICAO Air Navigation Regions. They are prepared on the authority of the Secretary General on the basis of recommendations of regional air navigation meetings and of the Council action thereon. The plans are amended periodically to reflect changes in requirements and in the status of implementation of the recommended facilities and services.

ICAO Circulars make available specialized information of interest to Contracting States. This includes studies on technical subjects.

© ICAO 1998 8/98, E/P1/5000

Order No. AN 6-2 Printed in ICAO

.